Revision: 05.08.2025



Safety data sheet according to UK REACH

Printing date 05.08.2025

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC_FujiCEM_2_Paste_A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax +32/(0)16/40.26.84

Fax +32/(0)16/40.26.84 msds@gc.dental

- _
- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms



· Signal word Warning

(Contd. on page 2)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC_FujiCEM_2_Paste_A

(Contd. of page 1)

· Hazard-determining components of labelling:

2-hydroxyethyl metacrylate

 $2,2'-ethylene dioxy die thyl\ dimethac rylate$

Urethane Dimethacrylate (UDMA)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl metacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<25%
CAS: 68909-20-6 EINECS: 272-697-1	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica STOT RE 2, H373, EUH066 Nanoform: set including amorphous nanoforms; surface-treated nanoforms; Spheroidal; amorphous forms; amorphous nanoform	5-<10%
CAS: 109-16-0 EINECS: 203-652-6 Index number: 607-768-00-1	2,2'-ethylenedioxydiethyl dimethacrylate Skin Sens. 1B, H317	5-<10%
CAS: 41637-38-1	Esterification products of 4,4'-isopropylidenediphenol, ethoxylated and 2-methylprop-2-enoic acid. Aquatic Chronic 4, H413	2.5-<5%
CAS: 72869-86-4 EINECS: 276-957-5 Index number: 607-767-00-6	Urethane Dimethacrylate (UDMA) Aquatic Chronic 2, H411; Skin Sens. 1B, H317	2.5-<5%

(Contd. on page 3)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC FujiCEM 2 Paste A

| (Contd. of page 2)
| Butylated hydroxytoluene | 0.1-<0.2%|

EINECS: 204-881-4 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

Substance identified as having endocrine disrupting properties (II)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

CAS: 128-37-0

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC FujiCEM 2 Paste A

(Contd. of page 3)

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· 6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELS	

128-37-0 Butylated hydroxytoluene

		•	-	
				0.5 mg/kg bw/day (man)
Inhalative	DNEL	inhalatio	on	3.5 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing

• Respiratory protection: Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC FujiCEM 2 Paste A

(Contd. of page 4)

· Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Characteristic

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

• Boiling point or initial boiling point and boiling range Undetermined. • Flammability Not applicable.

· Lower and upper explosion limit

Lower:

Lower:

Not determined.

Vupper:

Flash point:

Auto-ignition temperature:

Decomposition temperature:

Not determined.

Not determined.

Not determined.

Not determined.

· Viscosity:

• Kinematic viscosity
• Dynamic:

Not determined.

Not determined.

· Solubility

water: Insoluble.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density: Not determined.Relative density Not determined.

(Contd. on page 6)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC_FujiCEM_2_Paste_A

	(Contd. of page
Vapour density	Not determined.
Particle characteristics	SiO2: Diameter particle structure = 2.5 - 50 nm (TEM
	d50, number-based)
	Diameter agglomerate = $5 - 50$ mm (laser diffraction dr
	module, d50, volume based)
	68909-20-6 Silanamine, 1,1,1-trimethyl-N
	(trimethylsilyl)-, hydrolysis products with silica:
	set including amorphous nanoforms; surface-treate
	nanoforms; Spheroidal; amorphous forms; amorphou
	nanoform
9.2 Other information	
Appearance:	n.
Form:	Pasty
Important information on protection of hea	uth and
environment, and on safety.	Draduatic not calfigniting
Ignition temperature:	Product is not selfigniting. Product does not present an explosion hazard.
Explosive properties: Solvent content:	Froduct does not present an explosion nazara.
· VOC (EC)	$0.0~\mathrm{g/l}$
Change in condition	0.0 g/i
Evaporation rate	Not determined.
Information with regard to physical hazard cla	18868
Explosives	Void
Flammable gases	Void
· Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammab	
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void V
Corrosive to metals	Void V.: J
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC FujiCEM 2 Paste A

(Contd. of page 6)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

72869-86-4 Urethane Dimethacrylate (UDMA)

Oral LD50 >5,000 mg/kg (rat female) (OECD 401)

128-37-0 Butylated hydroxytoluene

Oral |LD50| >6,000 mg/kg (rat (f+m)) (OECD 401)

- Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

· 11.2 Information on other hazards

· Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

GE

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC_FujiCEM_2_Paste_A

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	not regulated	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	not regulated	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	not regulated	
14.4 Packing group		
ADR, IMDG, IATA	not regulated	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 9)

Printing date 05.08.2025 Version number 4 (replaces version 3) Revision: 05.08.2025

Trade name: GC FujiCEM 2 Paste A

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- · Relevant phrases
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

 $\label{lem:lem:aquatic convergence} \textit{Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard-Category 1}$

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

- · Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.





Printing date 30.11.2023 *Version number 3 (replaces version 2)* Revision: 30.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC FujiCEM_2_Paste_B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

Tartaric acid

· Hazard statements

H318 Causes serious eye damage.

(Contd. on page 2)

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC FujiCEM 2 Paste B

(Contd. of page 1)

· Precautionary statements

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Additional information:

1.2 % of the mixture consists of component(s) of unknown toxicity.

Contains 1.2 % of components with unknown hazards to the aquatic environment.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous compone	ents:	
CAS: 9003-01-4	Polyacrylic acid	25-<50%
	Eye Irrit. 2, H319	
CAS: 14808-60-7	Quartz	10-<25%
EINECS: 238-878-4		
	substance with a Community workplace exposure limit	
CAS: 87-69-4	Tartaric acid	5-<10%
EINECS: 201-766-0	Eye Dam. 1, H318	
CAS: 7631-86-9	silicon dioxide	2.5-<5%
EINECS: 231-545-4	Nanoform: set including amorphous nanoforms	
	non-surface-treated nanoforms	
	Shape: Spheroidal	
	Structure: amorphous forms	
	Crystallinity: amorphous nanoform	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eve contact:

Protect unharmed eye.

(Contd. on page 3)

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC FujiCEM 2 Paste B

(Contd. of page 2)

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· 6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection: Protect against electrostatic charges.

(Contd. on page 4)

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC FujiCEM 2 Paste B

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

14808-60-7 Quartz

WEL Long-term value: 0.1* mg/m³

respirable

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

GB

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC FujiCEM 2 Paste B

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Blue

· Odour: Characteristic
· Odour threshold: Not determined.
· Melting point/freezing point: Undetermined.
· Boiling point or initial boiling point and boiling range
· Flammability Not applicable.

· Lower and upper explosion limit

Lower:

Lower:

Not determined.

Upper:

Not applicable.

Auto-ignition temperature:

Undetermined.

Not determined.

Not applicable.

Undetermined.

Not determined.

Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

• water:
• Partition coefficient n-octanol/water (log value)
• Vapour pressure:

Insoluble.

Not determined.

Not determined.

· Density and/or relative density

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.

• Particle characteristics SiO2: Diameter particle structure = 2.5 - 50 nm (TEM,

d50, number-based)

Diameter agglomerate = 5 - 50 mm (laser diffraction dry

module, d50, volume based) 7631-86-9 silicon dioxide:

set including amorphous nanoforms non-surface-treated nanoforms

Shape: Spheroidal Structure: amorphous forms

Crystallinity: amorphous nanoform

· 9.2 Other information

· Appearance:

· Form: Pasty

Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

• Water: 36.4 %
 • VOC (EC) 0.0 g/l

· Change in condition

· Evaporation rate Not determined.

(Contd. on page 6)

(Contd. of page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC_FujiCEM_2_Paste_B

		(Conta. of page 3)
· Information with regard to physical hazard cla	isses	
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammab	le gases	
in contact with water	Void	
· Oxidising liquids	Void	

Void Void

Void

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Oxidising solids

Organic peroxidesCorrosive to metals

· Desensitised explosives

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

7631-86-9 silicon dioxide

Oral | LD50 | 10,000 mg/kg (rat (f+m))

- · Serious eye damage/irritation Causes serious eye damage.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

GB

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC_FujiCEM_2_Paste_B

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport informat	ion	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	not regulated	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	not regulated	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	not regulated	
· 14.4 Packing group · ADR, IMDG, IATA	not regulated	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.	

(Contd. on page 8)

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC FujiCEM 2 Paste B

(Contd. of page 7)

· UN "Model Regulation":

not regulated

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

- · Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

(Contd. on page 9)

Printing date 30.11.2023 Version number 3 (replaces version 2) Revision: 30.11.2023

Trade name: GC_FujiCEM_2_Paste_B

(Contd. of page 8)

* * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GR -