

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UNIFAST LC Liquid
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven

Tel. +32/(0)16/74.10.00Fax +32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms







GHS02

GHS07

CHSOO

· Signal word Danger

(Contd. on page 2)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

(Contd. of page 1)

· Hazard-determining components of labelling:

Methyl methacrylate

Urethane Dimethacrylate (UDMA) 2-(2H-benzotriazol-2-yl)-p-cresol

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

Dangerous components:		
CAS: 80-62-6	Methyl methacrylate	50-<75%
EINECS: 201-297-1 Index number: 607-035-00-6	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
	substance with a Community workplace exposure limit	
CAS: 72869-86-4	Urethane Dimethacrylate (UDMA)	10-<25%
EINECS: 276-957-5 Index number: 607-767-00-6	Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
CAS: 2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	0.5-<1%
EINECS: 219-470-5	Acute Tox. 3, H331; Aquatic Chronic 1, H410; Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST LC Liquid

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB ·

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST LC Liquid

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

80-62-6 Methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

· DNELs

80-62-6 Methyl methacrylate

Dermal DNEL dermal 13.67 mg/kg bw/day (man) (worker, l. te., syst.)
Inhalative DNEL inhalation 208 mg/m3 (air) (worker, l. te., syst.)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· Respiratory protection: Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

(Contd. of page 4)

· Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Fluid

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 100 °C

• Flammability Highly flammable.

Tummubutiy 111gmy

· Lower and upper explosion limit

Lower: 2.1 Vol %
 Upper: 12.5 Vol %
 Flash point: 10 °C
 Auto-ignition temperature: Undetermined.
 Decomposition temperature: Not determined

• **Decomposition temperature:**• **pH**Not determined.

Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

water: Insoluble.

Partition coefficient n-octanol/water (log value) Not determined.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C:

Relative density

Vapour density

0.9 g/cm³

Not determined.

Not determined.

(Contd. on page 6)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

(Contd. of page 5)

9.2 Other information

· Appearance:

· Form: Liquid

Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

· Solvent content:

 \cdot VOC (EC) 0.0 g/l

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures

· Substances and mixtures, which emit flammable gases

in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for	classification:	:
-------------------------------	-----------------	---

80-62-6 Methyl methacrylate

Oral LD50 6,000 mg/kg (rabbit)

(Contd. on page 7)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

		(Contd. of page 6)	
Dermal	LD50	>5,000 mg/kg (rab)	
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))	
72869-86-4	72869-86-4 Urethane Dimethacrylate (UDMA)		
Oral	LD50	>5,000 mg/kg (rat female) (OECD 401)	
2440-22-4	2-(2H-ben	zotriazol-2-yl)-p-cresol	
Oral	LD50	10,000 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	0.59 mg/l (rat (f+m))	

- · Skin corrosion/irritation Causes skin irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

· 11.2 Information on other hazards

· Endocrine	disrupting properties
120 27 0	D 4 . 1 4 1 1 4 - 1

128-37-0 Butylated hydroxytoluene

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

(Contd. of page 7)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name ADR	1247 METHYL METHACRYLATE MONOMI STABILIZED, ENVIRONMENTALLY HAZARDOUS
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Transport hazard class(es)	
ADR ***	
Class Label	3 (F1) Flammable liquids. 3
Class Label	3 Flammable liquids.
IATA	·
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D C

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

	(Contd. of page
Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.
14.7 Maritime transport in bulk according	to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
· · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
- · · · -	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOME.
C	STABILIZED, 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 10)

Printing date 16.08.2024 Version number 6 (replaces version 5) Revision: 16.08.2024

Trade name: UNIFAST_LC_Liquid

(Contd. of page 9)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.