

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 29.07.2024 Revision: 03.07.2024

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
 - · Trade name: Signum liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- · Informing department: E-Mail: msds@kulzer-dental.com
- 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Causes serious eye irritation. Eye Irrit. 2 H319

Skin Sens. 1 H317 May cause an allergic skin reaction.

H360Fd May damage fertility. Suspected of damaging the unborn child. Repr. 1B

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
 - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

propylidynetrimethanol, ethoxylated, esters with acrylic acid

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

1,4-butandioldimethacrylate

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 2-propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]]ester, reaction products with diethylamine

Hazard statements

H319 Causes serious eye irritation.

May cause an allergic skin reaction.

H360Fd May damage fertility. Suspected of damaging the unborn child. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use. P273 Avoid release to the environment.

(Contd. on page 2)



Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

(Contd. of page 1)

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

· Additional information:

14.8 % of the mixture consists of component(s) of unknown toxicity.

Contains 14.8 % of components with unknown hazards to the aquatic environment.

Restricted to professional users.

· 2.3 Other hazards -

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Product based on methacrylates

· Dangerous components:		
CAS: 28961-43-5 NLP: 500-066-5	propylidynetrimethanol, ethoxylated, esters with acrylic acid Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥10-<25%
CAS: 2082-81-7 EINECS: 218-218-1	1,4-butandioldimethacrylate Skin Sens. 1B, H317	<i>≥</i> 10- <i>≤</i> 25%
CAS: 72869-86-4 EINECS: 276-957-5 Index number: 607-134-00-4 Reg.nr.: 01-2120751202-68-xxxx	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate Aquatic Chronic 2, H411 Skin Sens. 1B, H317 EUH204	≥10-<25%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X Reg.nr.: 01-2119972295-29-xxxx	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 1B, H360Fd Aquatic Chronic 2, H411 Skin Sens. 1B, H317	1-<3%
CAS: 111497-86-0 EC number: 601-101-8 Reg.nr.: 01-2119961351-42-XXXX	2-propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)]]ester, reaction products with diethylamine Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317 EUH208	≥1-≤5%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - After inhalation Supply fresh air; consult doctor in case of symptoms.
 - After skin contact Instantly wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 5 (replaces version 4)

Revision: 03.07.2024

Trade name: Signum liquid

(Contd. of page 2)

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

- · Protective equipment: No special measures required.
- Additional information -

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures

 Avoid contact with eyes and skin.
- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

6.4 Reference to other sections

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

-

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep containers tightly sealed.
 - Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
 - · Storage
 - Requirements to be met by storerooms and containers: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions: Store cool (not above 25 °C).
- · 7.3 Specific end use(s) No further relevant information available.

GB



Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.

· DNELs			
2082-81-7	1,4-butandioldimethacı	ylate	
Oral	general population, long	term, systemic	2.5 mg/Kg (not defined)
Dermal	worker industrial, long tel	rm, systemic	4.2 mg/Kg/d (not defined)
	general population, long	term, systemic	2.5 mg/Kg/d (not defined)
Inhalative	worker professional, long	term, systemic	14.5 mg/m3 (not defined)
	general population, long	term, systemic	4.3 mg/m3 (not defined)
72869-86-	4 7,7,9(or 7,9,9)-trime bismethacrylate	thyl-4,13-diox	o-3,14-dioxa-5,12-diazahexadecane-1,16-diyl
Oral	general population, long	term, systemic	0.3 mg/Kg (not defined)
Dermal	worker industrial, long te	rm, systemic	1.3 mg/Kg/d (not defined)
	general population, long	term, systemic	0.7 mg/Kg/d (not defined)
Inhalative	worker industrial, long te	rm, systemic	3.3 mg/m3 (not defined)
	general population, long	term, systemic	0.6 mg/m3 (not defined)
75980-60-	8 diphenyl(2,4,6-trimeth	ylbenzoyl)phos	sphine oxide
Oral	general population, long	term, systemic	0.0833 mg/Kg (not defined)
Dermal	worker industrial, long te	rm, systemic	0.233 mg/Kg/d (not defined)
	general population, long term, systemic		0.0833 mg/Kg/d (not defined)
Inhalative	worker industrial, long te	rm, systemic	0.822 mg/m3 (not defined)
	general population, long term, systemic		0.145 mg/m3 (not defined)
· PNE	ECs .		
	1,4-butandioldimethacı	-	
freshwater	•	0.043 mg/l (not	•
marine wa		0.004 mg/l (not defined)	
sewage tre	eatment plant	2 mg/l (not defii	ned)
	dry weight, freshwater	3.12 mg/Kg (no	,
sediment,	dry weight, marine water		
soil, dry weight 0.573 mg/Kg (no			•
72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate			
freshwater 0.01 mg/l (not defined)			
marine water 0.001 mg/l (not defined)			
sewage treatment plant 3.61 mg/l (not defined)		defined)	
sediment, dry weight, freshwater 4.56 mg/Kg (not defined)			
			(Contd. on page



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

	(Contd. of page 4)
sediment, dry weight, marine water	0.46 mg/Kg (not defined)
soil, dry weight	0.91 mg/Kg (not defined)
75980-60-8 diphenyl(2,4,6-trimeth	ylbenzoyl)phosphine oxide
freshwater	0.0014 mg/l (not defined)
marine water	0.00014 mg/l (not defined)
sediment, dry weight, freshwater	0.115 mg/Kg (not defined)
sediment, dry weight, marine water	0.0115 mg/Kg (not defined)
soil, dry weight	0.0222 mg/Kg (not defined)

[·] Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
 - General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Hand protection

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

- · Eye/face protection Tightly sealed safety glasses.
- · Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Smell:
Fluid
Colourless
Ester-like

(Contd. on page 6)



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

(Contd. of page 5) Odour threshold: Not determined. · Melting point/freezing point: Not determined · Boiling point or initial boiling point and 100 °C boiling range · Flammability Not applicable. · Lower and upper explosion limit Lower: Not determined. Upper: Not determined. · Flash point: >100 °C (72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahéxadecane-1.16-diyl bismethacrylate) · Auto-ignition temperature: 265.0 °C Decomposition temperature: Not determined. ·SADT рΗ Not determined. · Viscosity: Not determined. Kinematic viscosity · Kinematic viscosity · dynamic: Not determined. Solubility · Water: Not miscible or difficult to mix Partition coefficient n-octanol/water (log Not determined. 40 hPa Steam pressure at 20 °C: · Vapour pressure: Density and/or relative density Density at 20 °C 0.850 g/cm³ Relative density Not determined. · Vapour density Not determined. No further relevant information available. · 9.2 Other information Appearance: Fluid Form: · Important information on protection of health and environment, and on safety. Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive. Solvent content: **VOC EU** Ĭ0.8 % · Solids content: · Change in condition Not determined. Evaporation rate · Information with regard to physical hazard classes **Explosives** Void Void Flammable gases · Aerosols Void · Oxidising gases Void · Gases under pressure Void

(Contd. on page 7)



Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

		(Contd. of page 6
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - · Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute tox	Acute toxicity Based on available data, the classification criteria are not met.			
· LD/LC	· LD/LC50 values that are relevant for classification:			
28961-43-5 p	28961-43-5 propylidynetrimethanol, ethoxylated, esters with acrylic acid			
Oral LD50	>2,000 mg/kg (rat) (OECD 401)			
Dermal LD50	>13,200 mg/kg (rabbit)			
2530-85-0 3-	rimethoxysilylpropyl methacrylate			
Oral LD50	>2,000 mg/kg (rat)			
Dermal LD50	>2,000 mg/kg (rabbit)			
2082-81-7 1,4	2082-81-7 1,4-butandioldimethacrylate			
Oral LD50	10,066 mg/kg (rat) (OECD 401)			
72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate				
Oral LD50	>5,000 mg/kg (rat) (OECD 401)			
Dermal LD50	>2,000 mg/kg (rat) (OECD 402)			

(Contd. on page 8)



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

		(Contd. of page 7)
68611-4		lane, dichlorodimethyl-, reaction products with silica
Oral	LD50	>5,000 mg/kg (rat)
75980-0	60-8 di	phenyl(2,4,6-trimethylbenzoyl)phosphine oxide
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
111497	-86-0 2 e	-propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

May damage fertility. Suspected of damaging the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
 - · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 Repr. 1B
- 11.2 Information on other hazards
- Endocrine disrupting properties
 128-37-0 2,6-di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· 12.1 Toxicity	1
· Aquatic t	oxicity:
2530-85-0 3-	trimethoxysilylpropyl methacrylate
EC50/48h	>100 mg/l (daphnia) (EU C2.)
LC50/96h	>100 mg/l (fish) (EU C.1)
2082-81-7 1,4	4-butandioldimethacrylate
EC50/21d	14.1 mg/L (daphnia) (OECD 211)
EC50/48h	32.5 mg/l (fish)
NOEC / 21d	5.09 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	9.79 mg/l (algae) (OECD 201)
NOEC / 72h	2.11 mg/l (algae) (OECD 201)
NOEC / 48h	25 mg/l (fish)

(Contd. on page 9)



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 5 (replaces version 4) Revision: 03.07.2024

Trade name: Signum liquid

	(Contd. of page 8
ErC10/72h	4.35 mg/L (algae) (OECD 201)
	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl pismethacrylate
EC50/48h	>1.2 mg/l (daphnia) (OECD 202)
LC50/96h	10.1 mg/l (fish) (OECD 203)
ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)
NOEC / 72h	0.21 mg/l (algae) (OECD 201)
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica
LC50/96h	>10,000 mg/l (fish) (OECD 203)
ErC50 / 72 h	>10,000 mg/l (algae) (OECD 201)
EC50 / 24h	>10,000 mg/l (daphnia) (OECD 202)
75980-60-8 c	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
EC50/48h	10,100 mg/l (algae)
	3.53 mg/l (daphnia) (OECD 202)
LC50/96h	1.4 mg/l (fish) (OECD 203)
ErC50 / 72 h	>2.01 mg/l (algae) (OECD 201)
ErC10/72h	1.56 mg/L (algae) (OECD 201)
12.2 Persiste	ence and degradability
2530-85-0 3-	trimethoxysilylpropyl methacrylate
Biodegradation	on 69 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)
2082-81-7 1,4	4-butandioldimethacrylate
•	on 84 % /28d (not defined) (OECD 310)
72869-86-4 7 b	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl pismethacrylate
•	on 22 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
Biodegradation	on 0-10 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)
	ımulative potential
	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
Bloconcentra	tion factor (BCF) 47-55 (not defined)

- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
 - · Additional ecological information:
 - General notes:

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

(Contd. on page 10)



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 29.07.2024 Revision: 03.07.2024

Trade name: Signum liquid

(Contd. of page 9)

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

- · Uncleaned packagings:
 - Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

SECTION 14: Transport information		
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.	
· Transport/Additional information:	-	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 5 (replaces version 4)

Revision: 03.07.2024

Trade name: Signum liquid

(Contd. of page 10)

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Causes skin irritation. H315

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360Fd May damage fertility. Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects. H411 H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

EUH208 Contains . May produce an allergic reaction.

· Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic

compounds)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation — Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B Repr. 1B: Reproductive toxicity – Category 1B

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.



Page 1/12

Tel.: +49 (0)800 4372522

Safety data sheet according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 30.07.2024 Revision: 03.07.2024

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
 - · Trade name: Signum opaque F
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

- · Informing department: E-Mail: msds@kulzer-dental.com
- · 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Causes serious eye irritation. Eye Irrit. 2 H319

Skin Sens. 1 H317 May cause an allergic skin reaction.

H360Fd May damage fertility. Suspected of damaging the unborn child. Repr. 1B

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
 - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling: Bisphenol A Diglycidylether Diacrylate (BADGE-DA) diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide propylidynetrimethanol, ethoxylated, esters with acrylic acid

methacrylic acid, monoester with propane-1,2-diol

triethylen glycol dimethacrylate

· Hazard statements

H319 Causes serious eye irritation.

May cause an allergic skin reaction. H317

H360Fd May damage fertility. Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use. P273 Avoid release to the environment. P280 Wear protective gloves / eye protection.

(Contd. on page 2)



Page 2/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024 Version number 6 (replaces version 5) Revision: 03.07.2024

Trade name: Signum opaque F

(Contd. of page 1)

P280 Wear protective clothing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

· Additional information:

Restricted to professional users.

2.3 Other hazards -

- · Results of PBT and vPvB assessment
 - · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Product based on methacrylates

Description: Proc	duct based on methacrylate	es	
· Dangerous comp	oonents:		
CAS: 55818-57-0 NLP: 500-130-2 Reg.nr.: 01-21194900	Bisphenol A L Aquatic Chro 020-53-XXXXSkin Sens. 1,	Diglycidylether Diacrylate (BADGE-DA) nic 2, H411 , H317	≥25-≤50%
CAS: 28961-43-5 NLP: 500-066-5	acid	rimethanol, ethoxylated, esters with acry 1319; Skin Sens. 1, H317 onic 3, H412	lic ≥10-<25%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-1 Reg.nr.: 01-2119490	Eye Irrit. 2, H	acid, monoester with propane-1,2-diol 1319; Skin Sens. 1, H317	≥1-≤5%
CAS: 109-16-0 EINECS: 203-652-6 Index number: 607-1 Reg.nr.: 01-2119969	Skin Sens. 11 34-00-4	col dimethacrylate B, H317	≥1-≤5%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-2 Reg.nr.: 01-2119972:	Repr. 1B, H3 03-00-X Aquatic Chro	onic 2, H411	>0-0.3%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water. In case of persistent symptoms consult doctor.

(Contd. on page 3)



Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024

Version number 6 (replaces version 5)

Revision: 03.07.2024

Trade name: Signum opaque F

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

• 5.2 Special hazards arising from the substance or mixture
Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

· Protective equipment: No special measures required.

· Additional information -

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with eyes and skin.
- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

6.4 Reference to other sections

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

-

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep containers tightly sealed.
 - Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
 - Storage
 - Requirements to be met by storerooms and containers: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions: Store cool (not above 25 °C).
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.

(Contd. on page 4)



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024 Version number 6 (replaces version 5) Revision: 03.07.2024

Trade name: Signum opaque F

				(Contd. of p
· DNI	ELs			
	0 Bisphenol A Diglycidy			
Dermal	worker industrial, long te	rm, systemic	17.5 mg/Kg/d (not defined)	
	worker industrial, long te		122.5 mg/m3 (not defined)	
	1 methacrylic acid, mor			
Oral		-	2.5 mg/Kg (not defined)	
Dermal	worker industrial, long te	•	4.2 mg/Kg/d (not defined)	
	general population, long	term, systemic	,	
Inhalative	worker industrial, long te	rm, systemic	14.7 mg/m3 (not defined)	
			8.8 mg/m3 (not defined)	
	triethylen glycol dimetha	acrylate		
Oral		-	8.33 mg/Kg (not defined)	
Dermal	worker industrial, long te		13.9 mg/Kg/d (not defined)	
	general population, long	-	1	
Inhalative	worker industrial, long te	rm, systemic	48.5 mg/m3 (not defined)	
			14.5 mg/m3 (not defined)	
	8 diphenyl(2,4,6-trimeth			
Oral			0.0833 mg/Kg (not defined)	
Dermal	worker industrial, long te		0.233 mg/Kg/d (not defined)	
	general population, long			
Inhalative	worker industrial, long te	•	0.822 mg/m3 (not defined)	
	general population, long	term, systemic	0.145 mg/m3 (not defined)	
·PNI	ECs			
55818-57-	0 Bisphenol A Diglycidy	lether Diacryl	ate (BADGE-DA)	
freshwate	r	0.1 mg/l (not a	lefined)	
marine wa	ter	0.01 mg/l (not	defined)	
intermedia	ite water release	1 mg/l (not dei	fined)	
sewage tre	eatment plant	10 mg/l (not de	efined)	
sediment,	dry weight, freshwater	35.8 mg/Kg (n	ot defined)	
soil, dry w	eight	71 mg/Kg (not	defined)	
27813-02-	1 methacrylic acid, mor			
freshwate	r	0.904 mg/l (no	t defined)	
marine wa	ter	0.904 mg/l (no	t defined)	
sewage tre	eatment plant	10 mg/l (not defined)		
sediment,	dry weight, freshwater	6.28 mg/Kg (not defined)		
sediment,	dry weight, marine water	r 6.28 mg/Kg (not defined)		
soil, dry w	~	0.727 mg/Kg (not defined)	
109-16-0	triethylen glycol dimetha	acrylate		
freshwate		0.016 mg/l (no		
marine wa	ter	0.002 mg/l (no	nt defined)	



Page 5/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024 Version number 6 (replaces version 5) Revision: 03.07.2024

Trade name: Signum opaque F

		(Contd. of page 4)
sewage treatment plant	1.7 mg/l (not defined)	
sediment, dry weight, fresh	water 0.185 mg/Kg (not defin	ned)
sediment, dry weight, marin	e water 0.018 mg/Kg (not defin	ned)
soil, dry weight	0.027 mg/Kg (not defin	ned)
75980-60-8 diphenyl(2,4,6	-trimethylbenzoyl)phosphine	oxide
freshwater	0.0014 mg/l (not define	ed)
marine water	0.00014 mg/l (not defir	ned)
sediment, dry weight, fresh	water 0.115 mg/Kg (not defin	ned)
sediment, dry weight, marin	e water 0.0115 mg/Kg (not def	ined)
soil, dry weight	0.0222 mg/Kg (not def	ined)

Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
 - General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

· Eye/face protection Tightly sealed safety glasses.

(Contd. on page 6)



Page 6/12

Safety data sheet according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 30.07.2024 Revision: 03.07.2024

Trade name: Signum opaque F

· Body protection: Light weight protective clothing

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Physical state Colour:

· Smell:

Odour threshold: · Melting point/freezing point:

· Boiling point or initial boiling point and boiling range

· Flammability

Lower and upper explosion limit

· Lower:

· Upper: · Flash point:

· Decomposition temperature:

·SADT · pH

Viscosity:

Kinematic viscosity

· Kinematic viscosity

· dynamic:

Solubility

· Water:

· Partition coefficient n-octanol/water (log

value)

· Steam pressure at 20 °C:

Vapour pressure:

Density and/or relative density

Density at 20 °C Relative density · Vapour density

· 9.2 Other information Appearance: Form:

> · Important information on protection of health and environment, and on safety.

Self-inflammability:

· Explosive properties:

Fluid Brown Pink

White Colourless Ester-like

Not determined. Not determined

100 °C

Not applicable.

Not determined. Not determined.

111 °C (27813-02-1 methacrylic acid, monoester

with propane-1,2-diol) Not determined.

Not determined.

Not determined.

Not determined.

Not miscible or difficult to mix

Not determined.

1.360 g/cm3 Not determined.

Not determined.

40 mbar

No further relevant information available.

Pasty

Product is not selfigniting. Product is not explosive.

Not determined.

(Contd. on page 7)



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024 Version number 6 (replaces version 5) Revision: 03.07.2024

Trade name: Signum opaque F

		(Contd. of p
· Solvent content:		
· VOC EU	g/l	
· Change in condition	3	
· Evaporation rate	Not determined.	
Information with regard to physical hazard	1	
classes		
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
 - · Acute toxicity Based on available data, the classification criteria are not met.
 - · LD/LC50 values that are relevant for classification:

EE010 E7 A Dion	hanal A Dialyaid	vlether Diacrylate	(BADCE DA)
- 220 I 0=27 =U DISDI	denoi a imaivcia	vieiner ijiactviale	IDAINTEIJAI

Oral	LD0	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD0	>2,000 mg/kg (rat) (OECD 402)

(Contd. on page 8)



Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 30.07.2024 Revision: 03.07.2024

Trade name: Signum opaque F

		(Contd. of page 7)
Sensitisation	sensitization	(human)
		(mouse) (LLNA)
28961-43-5 p	ropylidynetri	imethanol, ethoxylated, esters with acrylic acid
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>13,200 mg/kg (rabbit)
27813-02-1 n	nethacrylic a	cid, monoester with propane-1,2-diol
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit)
109-16-0 trie	thylen glycol	dimethacrylate
Oral	LD50	8,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (mouse)
75980-60-8 d	iphenyl(2,4,6	-trimethylbenzoyl)phosphine oxide
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · **Germ cell mutagenicity** Based on available data, the classification criteria are not met. · **Carcinogenicity** Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- May damage fertility. Suspected of damaging the unborn child.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
 - CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 1B
- · 11.2 Information on other hazards
 - · Endocrine disrupting properties

128-37-0 2,6-di-tert-butyl-p-cresol List II

SECTION 12: Ecological information

· 12.1 Toxicity

65997-17-3 Glaspulver	
EC50/72h >1,000 mg/l (daphnia)	
LC50/96h >1,000 mg/l (fish)	
ErC50 / 72 h >1,000 mg/l (algae)	
NOEC / 72h 1,000 mg/l (algae)	
1,000 mg/l (daphnia)	

(Contd. on page 9)



Page 9/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024 Version number 6 (replaces version 5) Revision: 03.07.2024

Trade name: Signum opaque F

55040 57 0 F	(Contd. of page	
	Bisphenol A Diglycidylether Diacrylate (BADGE-DA)	
EC50/72h	>110 mg/l (algae) (OECD 201)	
LC50/96h	>79 mg/l (fish) (OECD 203)	
	nethacrylic acid, monoester with propane-1,2-diol	
EC50/72h	>97.2 mg/l (algae)	
EC50/48h	>143 mg/l (daphnia) (OECD 202)	
	45.2 mg/l (daphnia) (OECD 211)	
	>97.2 mg/l (algae) (OECD 201)	
	>97.2 mg/l (algae) (OECD 201)	
LC50/48h	483 mg/L (fish)	
	thylen glycol dimethacrylate	
EC50/21d	51.9 mg/L (daphnia) (OECD 211)	
LC50/96h	16.4 mg/l (fish) (OECD 203)	
	32 mg/l (daphnia) (OECD 211)	
	rC50 / 72 h >100 mg/l (algae) (OECD 201)	
	18.6 mg/l (algae) (OECD 201)	
	72.8 mg/l (algae) (OECD 201)	
	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	
EC50/48h	10,100 mg/l (algae)	
	3.53 mg/l (daphnia) (OECD 202)	
LC50/96h	1.4 mg/l (fish) (OECD 203)	
	>2.01 mg/l (algae) (OECD 201)	
ErC10/72h	1.56 mg/L (algae) (OECD 201)	
	ence and degradability	
	nethacrylic acid, monoester with propane-1,2-diol	
	on 81 % /28d (not defined) (OECD 301C)	
	thylen glycol dimethacrylate	
	on 85 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)	
	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	
Biodegradation	on 0-10 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)	
	ımulative potential	
	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	
Bloconcentra	tion factor (BCF) 47-55 (not defined)	

- 12.4 Mobility in soil No further relevant information available. 12.5 Results of PBT and vPvB assessment PBT: Not applicable.

• vPvB: Not applicable.
• 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 10)



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024

Version number 6 (replaces version 5)

Revision: 03.07.2024

Trade name: Signum opaque F

(Contd. of page 9)

· 12.7 Other adverse effects

- · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
 - Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3082	
· 14.2 UN proper shipping name · IMDG, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Diglycidylether Diacrylate (BADGE-DA))	
· 14.3 Transport hazard class(es) · ADR		



· Class

· Label

9 (M6) Miscellaneous dangerous substances and articles.

9

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024

Version number 6 (replaces version 5)

Revision: 03.07.2024

Trade name: Signum opaque F

	(Contd. of page 1
· IMDG	
₹	
3	
Class	9 Miscellaneous dangerous substances an articles.
· Label	9
·IATA	
· Class	9 Miscellaneous dangerous substances an articles.
· Label	9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	No Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Kemler Number:	90
· EMS Number: · Stowage Category	F-A,S-F A
· 14.7 Maritime transport in bulk according to IN instruments	10 Not applicable.
· Transport/Additional information:	-
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inne packaging: 30 ml Maximum net quantity per oute packaging: 1000 ml
· Transport category · Tunnel restriction code	;3 (-)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inne



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2024

Version number 6 (replaces version 5)

Revision: 03.07.2024

Trade name: Signum opaque F

(Contd. of page 11)

Maximum net quantity per outer

packaging: 1000 ml

UN "Model Regulation": Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360Fd May damage fertility. Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects. H411

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.



Page 1/10

Tel.: +49 (0)800 4372522

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023 Version number 5 (replaces version 4) Revision: 13.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
 - · Trade name: Signum composite ...
 - · dentine, margin, enamel, effect
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Veneering resin
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Informing department: E-Mail: msds@kulzer-dental.com

· 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - · Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
 - · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

1,12-Dodecanediol dimethacrylate

7,7,9 (or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

triethylen glycol dimethacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

- 2.3 Other hazards -
 - Results of PBT and vPvB assessment
 - · **PBT:** Not applicable.
 - vPvB: Not applicable.

- GB



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023 Version number 5 (replaces version 4) Revision: 13.02.2023

Trade name: Signum composite ...

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
 - · Description: Product based on methacrylates

· Dangerous components:		
EINECS: 276-900-4	1,12-Dodecanediol dimethacrylate Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) Skin Sens. 1B, H317	≥10-<25%
EINECS: 276-957-5 Reg.nr.: 01-2120751202-68-xxxx S	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate Aquatic Chronic 2, H411 Skin Sens. 1B, H317 EUH204	≥10-<25%
	riethylen glycol dimethacrylate Skin Sens. 1B, H317	≥1-≤5%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · General information No special measures required.
 - · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact

Rinse opened eye for several minutes under running water. Then consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.
 - · Additional information -

GB



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023

Version number 5 (replaces version 4)

Trade name: Signum composite ...

(Contd. of page 2)

Revision: 13.02.2023

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with eyes and skin.
- · 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

6.4 Reference to other sections

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
 - Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
 - Storage
 - Requirements to be met by storerooms and containers: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Store cool (not above 25 °C).
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
 - Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.

	bismethacrylate	
Oral	general population, long term, systemic	0.3 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	1.3 mg/Kg/d (not defined)
	general population, long term, systemic	0.7 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	3.3 mg/m3 (not defined)
	general population, long term, systemic	0.6 mg/m3 (not defined)
109-16-0 t	riethylen glycol dimethacrylate	
Oral	general population, long term, systemic	8.33 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.9 mg/Kg/d (not defined)
	general population, long term, systemic	8.33 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	48.5 mg/m3 (not defined)
	general population, long term, systemic	14.5 mg/m3 (not defined)
Inhalative		• ,

bismethacrylate

freshwater 0.01 mg/l (not defined)

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023 Version number 5 (replaces version 4) Revision: 13.02.2023

Trade name: Signum composite ...

	(Contd. of page 3)
marine water	0.001 mg/l (not defined)
sewage treatment plant	3.61 mg/l (not defined)
sediment, dry weight, freshwater	4.56 mg/Kg (not defined)
sediment, dry weight, marine water	0.46 mg/Kg (not defined)
soil, dry weight	0.91 mg/Kg (not defined)
109-16-0 triethylen glycol dimeth	acrylate
freshwater	0.016 mg/l (not defined)
marine water	0.002 mg/l (not defined)
sewage treatment plant	1.7 mg/l (not defined)
sediment, dry weight, freshwater	0.185 mg/Kg (not defined)
sediment, dry weight, marine water	0.018 mg/Kg (not defined)
soil, dry weight	0.027 mg/Kg (not defined)
Additional information. The	lists that were valid during the compilation were used as basis

[·] Additional information: The lists that were valid during the compilation were used as basis.

- · 8.2 Exposure controls
 - · Appropriate engineering controls No further data; see item 7.
 - Individual protection measures, such as personal protective equipment
 - General protective and hygienic measures

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Hand protection

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Check protective gloves prior to each use for their proper condition.

recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

- Eye/face protection Tightly sealed safety glasses.
- · Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid
· Colour: Brown
White
Pink

Colourless Odourless

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023

Version number 5 (replaces version 4)

Trade name: Signum composite ...

(Contd. of page 4)

Revision: 13.02.2023

Not determined. Odour threshold: · Melting point/freezing point: Not determined

· Boiling point or initial boiling point and boiling range

· Flammability

· Lower and upper explosion limit

Lower: Upper:

· Flash point:

· Decomposition temperature:

SADT

pН

· Viscosity: · Kinematic viscosity

· dynamic: · Solubility

· Water:

Partition coefficient n-octanol/water (log

· Steam pressure at 20 °C: Density and/or relative density

· Density at 20 °C

Relative density · Vapour density

250 °C

Not applicable.

Not determined. Not determined.

>100 °C (72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-

1,16-diyl bismethacrylate)

Not determined.

Mixture is non-soluble (in water).

Not determined.

Not determined.

Not miscible or difficult to mix

Not determined.

40 hPa

1.450 g/cm3 Not determined. Not determined.

9.2 Other information

Appearance:

Form: · Important information on protection of

health and environment, and on safety.

· Self-inflammability: · Explosive properties:

· Solvent content: · VOC EU · Change in condition

Evaporation rate

Pasty

Product is not selfigniting. Product is not explosive.

No further relevant information available.

Not determined.

Not determined.

g/l

· Information with regard to physical hazard classes

Explosives · Flammable gases · Aerosols

· Oxidising gases Gases under pressure · Flammable liquids

· Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids

· Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water Void

Void Void Void

Void Void

Void Void Void

Void Void

Void

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023 Version number 5 (replaces version 4) Revision: 13.02.2023

Trade name: Signum composite ...

		(Contd. of page 5
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - Conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

71041	io toxi	city based on available data, the diassincation enteria are not met.
·L	D/LC5	0 values that are relevant for classification:
112945	-52-5 <i>A</i>	Amorphous silica
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit)
72829-0	9-5 1,	12-Dodecanediol dimethacrylate
Oral	LD0	>2,000 mg/kg (rat) (OECD 423)
72869-8		7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl
	bi	smethacrylate
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
2530-85	5-0 3-tr	imethoxysilylpropyl methacrylate
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
109-16-	0 trietl	hylen glycol dimethacrylate
Oral	LD50	8,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (mouse)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met. **Carcinogenicity** Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/10

(Contd. of page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023

Version number 5 (replaces version 4)

Revision: 13.02.2023

Trade name: Signum composite ...

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

· 12.1 Toxicity

· Aquatic t	oxicity:
112945-52-5	Amorphous silica
LC50/96h	>10,000 mg/l (fish) (OECD 203)
EC50 / 24h	>1,000 mg/l (daphnia)
	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyloismethacrylate
EC50/48h	>1.2 mg/l (daphnia) (OECD 202)
LC50/96h	10.1 mg/l (fish) (OECD 203)
ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)
NOEC / 72h	0.21 mg/l (algae) (OECD 201)
2530-85-0 3-	trimethoxysilylpropyl methacrylate
EC50/48h	>100 mg/l (daphnia) (EU C2.)
LC50/96h	>100 mg/l (fish) (EU C.1)
109-16-0 trie	thylen glycol dimethacrylate
EC50/21d	51.9 mg/L (daphnia) (OECD 211)
LC50/96h	16.4 mg/l (fish) (OECD 203)
NOEC / 21d	32 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>100 mg/l (algae) (OECD 201)
NOEC / 72h	18.6 mg/l (algae) (OECD 201)
EbC50 / 72h	72.8 mg/l (algae) (OECD 201)

· 12.2 Persistence and degradability

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

Biodegradation 22 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

2530-85-0 3-trimethoxysilylpropyl methacrylate

Biodegradation 69 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)

109-16-0 triethylen glycol dimethacrylate

Biodegradation 85 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects No further relevant information available.

GB



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023

Version number 5 (replaces version 4)

Trade name: Signum composite ...

(Contd. of page 7)

Revision: 13.02.2023

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packagings:

• Recommendation:
Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

14.1 UN number or ID number	
· ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name · ADR	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (1,12 Dodecanediol dimethacrylate, 7,7,9(or 7,9,9 trimethyl-4,13-dioxo-3,14-dioxa-5,12 diazahexadecane-1,16-diyl bismethacrylate)
· IMDG	ENVIRONMENTALLY HAZÁRDOU SUBSTANCE, LIQUID, N.O.S. (1,12 Dodecanediol dimethacrylate, 7,7,9(or 7,9,9 trimethyl-4,13-dioxo-3,14-dioxa-5,12 diazahexadecane-1,16-diyl bismethacrylate MARINE POLLUTANT
·IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (1,12 Dodecanediol dimethacrylate, 7,7,9(or 7,9,9 trimethyl-4,13-dioxo-3,14-dioxa-5,12 diazahexadecane-1,16-diyl bismethacrylate)
14.3 Transport hazard class(es)	
· ADR	
· Class · Label	9 (M6) Miscellaneous dangerous substance and articles.
	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances ar articles.



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023

Version number 5 (replaces version 4)

Revision: 13.02.2023

Trade name: Signum composite ...

	(Contd. of page
· Label	9
14.4 Packing group ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances ar articles.
· Kemler Number: · EMS Number: · Stowage Category	90 F-A,S-F A
· 14.7 Maritime transport in bulk according IMO instruments	g to Not applicable.
Transport/Additional information:	-
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packagin 30 ml Maximum net quantity per outer packagin 1000 ml
· Transport category · Tunnel restriction code	3 (-)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packagin 30 ml Maximum net quantity per outer packagin 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (1,12 DODECANEDIOL DIMETHACRYLATE, 7,7,9(C 7,9,9)-TRIMETHYL-4,13-DIOXO-3,14-DIOXA 5,12-DIAZAHEXADECANE-1,16-DIY BISMETHACRYLATE), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.02.2023

Version number 5 (replaces version 4)

Trade name: Signum composite ...

(Contd. of page 9)

Revision: 13.02.2023

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement

Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.

GB



Page 1/10

Revision: 17.11.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
 - · Trade name: Signum composite flow
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Veneering resin
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany) Tel.: +49 (0)800 4372522

- · Informing department: E-Mail: msds@kulzer-dental.com
- · 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - · Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
 - · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

triethylen glycol dimethacrylate

methyl methacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· 2.3 Other hazards -

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
 - · Description: -
 - · Dangerous components:

CAS: 109-16-0

EINECS: 203-652-6

triethylen glycol dimethacrylate Skin Sens. 1B, H317

Reg.nr.: 01-2119969287-21-xxxx

≥10-*≤*25%

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022 Version number 4 (replaces version 3) Revision: 17.11.2022

Trade name: Signum composite flow

	(C	ontd. of page 1)
CAS: 41637-38-1 EC number: 609-946-4	bisphenol a polyethylene glycol diether dimethacrylate Aquatic Chronic 4, H413	≥0-≤5%
CAS: 131-57-7	Oxybenzone	≥0.25-<1%
EINECS: 205-031-5	Aquatic Acute 1, H400; Aquatic Chronic 2, H411	
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Lig. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3,	≥0.1-<1%
	Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.
 - Additional information -

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Do not allow to enter the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues). Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

See Section 13 for information on disposal.

(Contd. of page 2)

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Wear protective equipment. Keep unprotected persons away. Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities Storage
 - Requirements to be met by storerooms and containers: No special requirements. Information about storage in one common storage facility: Not required.

 - · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Compo	onents with cri	tical values that require	monitoring at the workplace:	
80-62-6 m	ethyl methacry	ylate		
WEL (Great Britain)		Short-term value: 416 m	g/m³, 100 ppm	
		Long-term value: 208 mg/m³, 50 ppm		
IOELV (Ει	ıropean Union)	Short-term value: 100 ppm		
		Long-term value: 50 ppn	7	
· DNI				
	, ,	ol dimethacrylate		
Oral	•	tion, long term, systemic	, , , , , , , , , , , , , , , , , , ,	
Dermal	worker industrial, long term, systemic		13.9 mg/Kg/d (not defined)	
	general popula	tion, long term, systemic	8.33 mg/Kg/d (not defined)	
Inhalative	worker industrial, long term, systemic		48.5 mg/m3 (not defined)	
	general popula	tion, long term, systemic	14.5 mg/m3 (not defined)	
41637-38-	1 bisphenol a	polyethylene glycol die	ther dimethacrylate	
Oral	general population, long term, systemic		5 mg/Kg (not defined)	
Dermal	worker industri	al, long term, systemic	140 mg/Kg/d (not defined)	
	general popula	tion, long term, systemic	50 mg/Kg/d (not defined)	
Inhalative	worker industrial, long term, systemic		98.7 mg/m3 (not defined)	
	general popula	tion, long term, systemic	17.4 mg/m3 (not defined)	
131-57-7 (Oxybenzone			
Oral	general population, long term, systemic		2 mg/Kg (not defined)	
Dermal	worker industrial, long term, systemic		39 mg/Kg/d (not defined)	
	general popula	tion, long term, systemic	20 mg/Kg/d (not defined)	
Inhalative	worker industrial, long term, systemic		27.7 mg/m3 (not defined)	
	general popula	tion, long term, systemic	6.8 mg/m3 (not defined)	
80-62-6 m	ethyl methacry	ylate		
Oral	general popula	tion, long term, systemic	8.2 mg/Kg (not defined)	
Dermal	worker industri	al, long term, systemic	13.67 mg/Kg/d (not defined)	
		tion, long term, systemic	8.2 mg/Kg/d (not defined)	



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022 Version number 4 (replaces version 3) Revision: 17.11.2022

Trade name: Signum composite flow

				(2) 5 6
Inhalative	Inhalative worker industrial, acute, le		416 mg/m3 (not defined)	(Contd. of page 3
	worker industrial, long teri		348.4 mg/m3 (not defined)	
	worker industrial, long te		208 mg/m3 (not defined)	
	general population, acute		208 mg/m3 (not defined)	
	general population, long		,	
· PNI	ECs			
109-16-0 1	triethylen glycol dimetha	acrylate		
freshwater	r	0.016 mg/l (no	t defined)	
marine wa	ter	0.002 mg/l (no	t defined)	
sewage tre	eatment plant	1.7 mg/l (not d	lefined)	
sediment,	dry weight, freshwater	0.185 mg/Kg (l	0.185 mg/Kg (not defined)	
sediment,	dry weight, marine water	0.018 mg/Kg (not defined)		
soil, dry w	eight	0.027 mg/Kg (not defined)		
131-57-7 (131-57-7 Oxybenzone			
freshwater	r	0.00067 mg/l (not defined)	
marine wa	ter	0.000067 mg/l (not defined)		
sewage tre	eatment plant	10 mg/l (not defined)		
sediment,	dry weight, freshwater	0.066 mg/Kg (l	not defined)	
sediment,	dry weight, marine water	0.007 mg/Kg (l	not defined)	
soil, dry w	soil, dry weight		not defined)	
80-62-6 m	80-62-6 methyl methacrylate			
freshwater	freshwater		defined)	
marine wa	marine water		t defined)	
sewage tre	eatment plant	10 mg/l (not de	efined)	
sediment,	dry weight, freshwater	10.2 mg/Kg (n	ot defined)	
sediment,	sediment, dry weight, marine water		not defined)	
soil, dry w	eight	1.48 mg/Kg (n	ot defined)	

Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- · Individual protection measures, such as personal protective equipment
 - General protective and hygienic measures

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- Hand protection

Check protective gloves prior to each use for their proper condition. recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022 Version number 4 (replaces version 3) Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 4)

· Eye/face protection Safety glasses

· Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Physical state Fluid · Colour: Brown White

VVnite
Pink
Colourless
Odourless

· Smell: Odourless

· Odour threshold: Not determined. Not determined. Not determined

Boiling point or initial boiling point and

boiling range 255 °C Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.

· Flash point: >100 °C (109-16-0 triethylen glycol

dimethacrylate) Not determined.

Decomposition temperature:

·SADT

• **pH** Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity
· dynamic:
Solubility

Not determined.
Not determined.

Motor

• Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

value) Not determined. Steam pressure: Not determined.

Density and/or relative density

Density
 Relative density
 Vapour density
 Not determined.
 Not determined.

• **9.2 Other information** No further relevant information available.

· Appearance:

Form: Fluid Important information on protection of

health and environment, and on safety.

Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

Not determined.

· Solvent content:

Water: 1.3 % Solids content: 9.6 %

Change in condition

· Evaporation rate Not determined.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3) Printing date 17.11.2022 Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 5)

Information with regard to physical hazard classes	
	Maid
Explosives	Void
· Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Conditions to be avoided: No decomposition if used and stored according to specifications. 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available. 10.6 Hazardous decomposition products: None
- - Additional information: -

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

7.00.0	ricute textority baccar on available data, the classification of the motion		
· LD/	· LD/LC50 values that are relevant for classification:		
109-16-0	triethylen	glycol dimethacrylate	
Oral	LD50	8,300 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (mouse)	
68611-44	9 Silane,	dichlorodimethyl-, reaction products with silica	
Oral	LD50	>5,000 mg/kg (rat)	
Inhalative	LC0/4h	0.477 mg/L (rat)	
41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate			
Oral	LD50	>2,000 mg/kg (rat) (OECD 423)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	
131-57-7 Oxybenzone			
Oral	LD50	>12,800 mg/kg (rat) (OECD 401)	
Dermal	LD50	>16,000 mg/kg (rabbit) (OECD 402)	
	•		(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Trade name: Signum composite flow

(Contd. of page 6)

Revision: 17.11.2022

80-62-6 methyl methacrylate	è
-----------------------------	---

Oral LD50 ~7,900 mg/kg (rat)

LD50 >5,000 mg/kg (guinea pig) (OECD 402) Dermal

Inhalative LC50/4 h 29.8 mg/l (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
 Carcinogenicity Based on available data, the classification criteria are not met.
 Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
 - · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

•	<i>12.1</i>	<i>i oxicity</i>	,

	· 12.1 Toxicity				
	· Aquatic toxicity:				
65997-17-3 G	65997-17-3 Glaspulver				
EC50/72h	>1,000 mg/l (daphnia)				
LC50/96h	>1,000 mg/l (fish)				
ErC50 / 72 h	>1,000 mg/l (algae)				
NOEC / 72h	1,000 mg/l (algae)				
	1,000 mg/l (daphnia)				
109-16-0 trie	thylen glycol dimethacrylate				
EC50/21d	51.9 mg/L (daphnia) (OECD 211)				
LC50/96h	16.4 mg/l (fish) (OECD 203)				
NOEC / 21d	32 mg/l (daphnia) (OECD 211)				
ErC50 / 72 h	>100 mg/l (algae) (OECD 201)				
NOEC / 72h	18.6 mg/l (algae) (OECD 201)				
EbC50 / 72h	72.8 mg/l (algae) (OECD 201)				
68611-44-9 S	ilane, dichlorodimethyl-, reaction products with silica				
LC50/96h	>10,000 mg/l (fish) (OECD 203)				
ErC50 / 72 h	>10,000 mg/l (algae) (OECD 201)				
EC50 / 24h	>10,000 mg/l (daphnia) (OECD 202)				
41637-38-1 b	isphenol a polyethylene glycol diether dimethacrylate				
LL50/96h	>100 mg/L (fish) (OECD 203)				
EL50/48h	>100 mg/L (daphnia) (OECD 202)				
EL50/72h	>100 mg/L (algae) (OECD 201)				
NOEC / 21d	≥0.00224 mg/l (daphnia) (OECD 211)				
131-57-7 Oxy	/benzone				
EC50/48h	1.87 mg/l (daphnia) (OECD 202)				
	(Contd. on page 8)				



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022 Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

	(Contd. of page 7)
LC50/96h	3.8 mg/l (fish) (OECD 203)
ErC50 / 72 h	0.67 mg/l (algae) (OECD 201)
NOEC / 72h	0.18 mg/l (algae) (OECD 201)
NOEC / 96h	0.72 mg/l (fish) (OECD 203)
	1.15 mg/l (daphnia) (OECD 202)
80-62-6 meth	nyl methacrylate
EC50/21d	49 mg/L (daphnia) (OECD 211)
EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)
NOEC / 21d	37 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)
NOEC / 72h	110 mg/l (algae) (OECD 201)
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)
EbC50 / 72h	>110 mg/l (algae) (OECD 201)
NOEC/ 35d	9.4 mg/L (fish) (OECD 210)
LC50/ 35d	33.7 mg/L (fish) (OECD 210)
· 12.2 Persiste	ence and degradability
109-16-0 trie	thylen glycol dimethacrylate
Biodegradation	on 85 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
41637-38-1 b	pisphenol a polyethylene glycol diether dimethacrylate
Biodegradation	on 24 % /28d (not defined) (OECD 301D)
131-57-7 Oxy	ybenzone
	on 60-70 % /28d (not defined)
	nyl methacrylate
Biodegradation	on 94 % /14d (not defined) (OECD 301C)
12.3 Bioaccu	umulative potential
131-57-7 Oxy	vbenzone

131-57-7 Oxybenzone

Bloconcentration factor (BCF) | >33-<160 (fish) (OECD 305)

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
 - · Remark: Harmful to fish
 - Additional ecological information:
 - · General notes:

Avoid transfer into the environment. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 8)

· Uncleaned packagings:

· Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.	
· Transport/Additional information:	-	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chamical Abstracts Society (division of the American Chemical Society)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids — Category 2
Skin Irrit. 2: Skin corrosion/irritation — Category 2
Skin Sens. 1: Skin sensitisation — Category 1
Skin Sens. 1B: Skin sensitisation — Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) — Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 4
** Data compared to the previous version altered.



Page 1/9

Revision: 16.11.2022

Tel.: +49 (0)800 4372522

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
 - · Trade name: Signum matrix Matrix, Opal, MD, SD
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Veneering resin
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Informing department: E-Mail: msds@kulzer-dental.com

· 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
 - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

triethylen glycol dimethacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

- · 2.3 Other hazards -
 - Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
 - · Description: Product based on methacrylates

Dangerous components:

CAS: 109-16-0 EINECS: 203-652-6

triethylen glycol dimethacrylate

Skin Sens. 1B, H317

Reg.nr.: 01-2119969287-21-xxx

≥10-≤25%

(Contd. on page 2)



Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022 Version number 4 (replaces version 3) Revision: 16.11.2022

Trade name: Signum matrix Matrix, Opal, MD, SD

(Contd. of page 1)

CAS: 131-57-7 Oxybenzone

≥0.25-<1%

EINECS: 205-031-5

Aquatic Acute 1, H400; Aquatic Chronic 2, H411

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.
 - · Additional information -

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with eyes and skin.
- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

-

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
 - Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
 - · Storage
 - Requirements to be met by storerooms and containers: No special requirements.

(Contd. on page 3)



Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022

Version number 4 (replaces version 3)

Trade name: Signum matrix Matrix, Opal, MD, SD

(Contd. of page 2)

Revision: 16.11.2022

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store cool (not above 25 °C).
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.					
· DNELs					
109-16-0 triethylen glycol dimethacrylate					
Oral	general population, long term, systemic	8.33 mg/Kg (not defined)			
Dermal	worker industrial, long term, systemic	13.9 mg/Kg/d (not defined)			
	general population, long term, systemic	8.33 mg/Kg/d (not defined)			
Inhalative	worker industrial, long term, systemic	48.5 mg/m3 (not defined)			
	general population, long term, systemic	14.5 mg/m3 (not defined)			
41637-38-	1 bisphenol a polyethylene glycol die	ther dimethacrylate			
Oral	general population, long term, systemic	5 mg/Kg (not defined)			
Dermal	worker industrial, long term, systemic	140 mg/Kg/d (not defined)			
	general population, long term, systemic	50 mg/Kg/d (not defined)			
Inhalative	worker industrial, long term, systemic	98.7 mg/m3 (not defined)			
	general population, long term, systemic	17.4 mg/m3 (not defined)			
131-57-7 (Oxybenzone				
Oral	general population, long term, systemic	2 mg/Kg (not defined)			
Dermal	worker industrial, long term, systemic	39 mg/Kg/d (not defined)			
	general population, long term, systemic	20 mg/Kg/d (not defined)			
Inhalative	worker industrial, long term, systemic	27.7 mg/m3 (not defined)			
	general population, long term, systemic	6.8 mg/m3 (not defined)			
80-62-6 m	ethyl methacrylate				
Oral	general population, long term, systemic	8.2 mg/Kg (not defined)			
Dermal	worker industrial, long term, systemic	13.67 mg/Kg/d (not defined)			
	general population, long term, systemic	8.2 mg/Kg/d (not defined)			
Inhalative	worker industrial, acute, local	416 mg/m3 (not defined)			
	worker industrial, long term, systemic	348.4 mg/m3 (not defined)			
	worker industrial, long term, local	208 mg/m3 (not defined)			
	general population, acute, local	208 mg/m3 (not defined)			
	general population, long term, systemic	74.3 mg/m3 (not defined)			
· PNI	FCe				

PNECs

109-16-0 triethylen glycol dimethacrylate

0.016 mg/l (not defined) freshwater 0.002 mg/l (not defined) marine water sewage treatment plant 1.7 mg/l (not defined) sediment, dry weight, freshwater 0.185 mg/Kg (not defined)

(Contd. on page 4)



Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022 Version number 4 (replaces version 3) Revision: 16.11.2022

Trade name: Signum matrix Matrix, Opal, MD, SD

	(Contd. of page 3
sediment, dry weight, marine water	0.018 mg/Kg (not defined)
soil, dry weight	0.027 mg/Kg (not defined)
131-57-7 Oxybenzone	
freshwater	0.00067 mg/l (not defined)
marine water	0.000067 mg/l (not defined)
sewage treatment plant	10 mg/l (not defined)
sediment, dry weight, freshwater	0.066 mg/Kg (not defined)
sediment, dry weight, marine water	0.007 mg/Kg (not defined)
soil, dry weight	0.013 mg/Kg (not defined)
80-62-6 methyl methacrylate	
freshwater	0.94 mg/l (not defined)
marine water	0.094 mg/l (not defined)
sewage treatment plant	10 mg/l (not defined)
sediment, dry weight, freshwater	10.2 mg/Kg (not defined)
sediment, dry weight, marine water	0.102 mg/Kg (not defined)
soil, dry weight	1.48 mg/Kg (not defined)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
 - General protective and hygienic measures

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition. recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

- Eye/face protection Tightly sealed safety glasses.
- · Body protection: Light weight protective clothing

- GI



Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022 Version number 4 (replaces version 3) Revision: 16.11.2022

Trade name: Signum matrix Matrix, Opal, MD, SD

Gases under pressure

· Flammable liquids

Flammable solids

(Contd. of page 4)

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties **General Information** · Physical state Fluid · Colour: Beige · Smell: Odourless Odour threshold: Not determined. · Melting point/freezing point: Not determined · Boiling point or initial boiling point and 250 °C boiling range · Flammability Not applicable. · Lower and upper explosion limit Not determined. Lower: Not determined. Upper: >150 °C (109-16-0 triethylen glycol dimethacrylate) · Flash point: · Decomposition temperature: Not determined. SADT · pH Not determined. Viscosity: Not determined. · Kinematic viscosity dynamic: Not determined. Solubility Not miscible or difficult to mix Water: · Partition coefficient n-octanol/water (log Not determined. value) · Steam pressure: Not determined. Density and/or relative density Not determined · Density Relative density Not determined. · Vapour density Not determined. No further relevant information available. · 9.2 Other information Appearance: Fluid Form: · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive. Not determined. · Solvent content: 2.3-<3.7 % · Water: Solids content: 0.0 % Change in condition Not determined. · Evaporation rate · Information with regard to physical hazard classes Void **Explosives** · Flammable gases Void · Aerosols Void · Oxidising gases Void

Void

Void

Void



Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022 Version number 4 (replaces version 3) Revision: 16.11.2022

Trade name: Signum matrix Matrix, Opal, MD, SD

		(Contd. of page 5)
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
 - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - · Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
109-16-0 1	triethylen	glycol dimethacrylate
Oral	LD50	8,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (mouse)
68611-44-	9 Silane, o	dichlorodimethyl-, reaction products with silica
Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC0/4h	0.477 mg/L (rat)
41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate		
Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
131-57-7	Oxybenzo	ne
Oral	LD50	>12,800 mg/kg (rat) (OECD 401)
Dermal	LD50	>16,000 mg/kg (rabbit) (OECD 402)
80-62-6 m	ethyl met	hacrylate
Oral	LD50	~7,900 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)
Inhalative	LC50/4 h	29.8 mg/l (rat)
. Ckin o		ritation Research available data, the election criteria are not mot

Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022

Version number 4 (replaces version 3)

Trade name: Signum matrix Matrix, Opal, MD, SD

(Contd. of page 6)

Revision: 16.11.2022

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation

- May cause an allergic skin reaction.

 Germ cell mutagenicity Based on available data, the classification criteria are not met.

 Carcinogenicity Based on available data, the classification criteria are not met.

- Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
 - Endocrine disrupting properties

None of the ingredients is listed.

LC50/96h	12.1 Toxicity	•	
Section Sect	Aquatic to	oxicity:	
LC50/96h >1,000 mg/l (fish) >1,000 mg/l (algae) 1,000 mg/l (daphnia) CECD 2011	65997-17-3	Glaspulver	
ErC50 / 72 h	EC50/72h	>1,000 mg/l (daphnia)	
1,000 mg/l (daphnia)	LC50/96h	>1,000 mg/l (fish)	
109-16-0 triethylen glycol dimethacrylate	ErC50 / 72 h	>1,000 mg/l (algae)	
109-16-0 triethylen glycol dimethacrylate EC50/21d 51.9 mg/L (daphnia) (OECD 211) 16.4 mg/l (fish) (OECD 203) 32 mg/l (daphnia) (OECD 211) >100 mg/l (algae) (OECD 201) 18.6 mg/l (algae) (OECD 201) 19.000 mg/l (fish) (OECD 203) 10.000 mg/l (algae) (OECD 201) 10.000 mg/l (daphnia) (OECD 202) 10.000 mg/l (daphnia) (OECD 202) 10.000 mg/l (fish) (OECD 203) 10.000 mg/l (daphnia) (OECD 202) 10.000 mg/l (algae) (OECD 201) 10.000 mg/l (algae) (OECD 203) 10.000 mg/l (algae) (OECD 201) 10.000 mg/l (algae) (OECD 203)	NOEC / 72h	1,000 mg/l (algae)	
EC50/21d 51.9 mg/L (daphnia) (OECD 211) LC50/96h 16.4 mg/l (fish) (OECD 203) NOEC / 21d 32 mg/l (daphnia) (OECD 211) ErC50 / 72 h >100 mg/l (algae) (OECD 201) NOEC / 72h 18.6 mg/l (algae) (OECD 201) EbC50 / 72h 72.8 mg/l (algae) (OECD 201) 68611-44-9 Silane, dichlorodimethyl-, reaction products with silica LC50/96h >10,000 mg/l (fish) (OECD 203) ErC50 / 72 h >10,000 mg/l (algae) (OECD 201) EC50 / 24h >10,000 mg/l (daphnia) (OECD 202) 41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h 1.87 mg/l (daphnia) (OECD 202) EC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 72h 0.72 mg/l (fish) (OECD 203)		1,000 mg/l (daphnia)	
LC50/96h 16.4 mg/l (fish) (OECD 203) NOEC / 21d 32 mg/l (daphnia) (OECD 211) ErC50 / 72 h >100 mg/l (algae) (OECD 201) NOEC / 72h 18.6 mg/l (algae) (OECD 201) EbC50 / 72h 72.8 mg/l (algae) (OECD 201) E8611-44-9 Silane, dichlorodimethyl-, reaction products with silica LC50/96h >10,000 mg/l (fish) (OECD 203) ErC50 / 72 h >10,000 mg/l (algae) (OECD 201) EC50 / 24h >10,000 mg/l (daphnia) (OECD 202) 41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h	109-16-0 trie	thylen glycol dimethacrylate	
NOEC / 21d 32 mg/l (daphnia) (OECD 211) 2100 mg/l (algae) (OECD 201) 2100 mg/l (algae) (OECD 201) 21.8 mg/l (algae) (OECD 201) 22.8 mg/l (algae) (OECD 203) 21.0,000 mg/l (fish) (OECD 203) 21.0,000 mg/l (algae) (OECD 201) 22.50 / 24h 21.0,000 mg/l (algae) (OECD 202) 24.637-38-1 bisphenol a polyethylene glycol diether dimethacrylate 21.50/96h 21.00 mg/L (fish) (OECD 203) 21.00 mg/L (algae) (OECD 201) 20.00224 mg/l (daphnia) (OECD 201) 20.00224 mg/l (daphnia) (OECD 211) 21.50/96h 21.87 mg/l (daphnia) (OECD 202) 21.87 mg/l (daphnia) (OECD 203) 21.50/96h 21.87 mg/l (daphnia) (OECD 203) 21.50/96h 21.87 mg/l (algae) (OECD 201) 21.50/96h 21.50/96h	EC50/21d	51.9 mg/L (daphnia) (OECD 211)	
ErC50 / 72 h	LC50/96h	16.4 mg/l (fish) (OECD 203)	
NOEC / 72h 18.6 mg/l (algae) (OECD 201) EbC50 / 72h 72.8 mg/l (algae) (OECD 201) 68611-44-9 Silane, dichlorodimethyl-, reaction products with silica LC50/96h >10,000 mg/l (fish) (OECD 203) ErC50 / 72 h >10,000 mg/l (algae) (OECD 201) EC50 / 24h >10,000 mg/l (daphnia) (OECD 202) 41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (algae) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h 1.87 mg/l (daphnia) (OECD 202) LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203) CFC50/96h 0.72 mg/l (fish) (OECD 203)	NOEC / 21d	32 mg/l (daphnia) (OECD 211)	
EbC50 / 72h	ErC50 / 72 h	>100 mg/l (algae) (OECD 201)	
68611-44-9 Silane, dichlorodimethyl-, reaction products with silica LC50/96h >10,000 mg/l (fish) (OECD 203) ErC50 / 72 h >10,000 mg/l (algae) (OECD 201) EC50 / 24h >10,000 mg/l (daphnia) (OECD 202) 41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h EC50/48h 1.87 mg/l (daphnia) (OECD 202) LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)	NOEC / 72h	18.6 mg/l (algae) (OECD 201)	
LC50/96h >10,000 mg/l (fish) (OECD 203) ErC50 / 72 h >10,000 mg/l (algae) (OECD 201) EC50 / 24h >10,000 mg/l (daphnia) (OECD 202) 41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h 1.87 mg/l (daphnia) (OECD 202) LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)	EbC50 / 72h	72.8 mg/l (algae) (OECD 201)	
ErC50 / 72 h	68611-44-9 S	• • •	
EC50 / 24h	LC50/96h	>10,000 mg/l (fish) (OECD 203)	
41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h 1.87 mg/l (daphnia) (OECD 202) LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)	ErC50 / 72 h	>10,000 mg/l (algae) (OECD 201)	
LL50/96h >100 mg/L (fish) (OECD 203) EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h			
EL50/48h >100 mg/L (daphnia) (OECD 202) EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h	41637-38-1 b		
EL50/72h >100 mg/L (algae) (OECD 201) NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h	LL50/96h	• , , ,	
NOEC / 21d ≥0.00224 mg/l (daphnia) (OECD 211) 131-57-7 Oxybenzone EC50/48h 1.87 mg/l (daphnia) (OECD 202) LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)	EL50/48h		
131-57-7 Oxybenzone EC50/48h 1.87 mg/l (daphnia) (OECD 202) LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)			
EC50/48h			
LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h 0.67 mg/l (algae) (OECD 201) NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)	•		
ErC50 / 72 h		÷ , , , , ,	
NOEC / 72h 0.18 mg/l (algae) (OECD 201) NOEC / 96h 0.72 mg/l (fish) (OECD 203)			
NOEC / 96h 0.72 mg/l (fish) (OECD 203)			
	NOEC / 72h	0.18 mg/l (algae) (OECD 201)	
	NOEC / 96h	0.72 mg/l (fish) (OECD 203)	
		(C	contd. on p



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022 Version number 4 (replaces version 3) Revision: 16.11.2022

Trade name: Signum matrix Matrix, Opal, MD, SD

		(Contd. of page 7)				
	80-62-6 meth	nyl methacrylate				
	EC50/21d	49 mg/L (daphnia) (OECD 211)				
	EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)				
	NOEC / 21d	37 mg/l (daphnia) (OECD 211)				
	ErC50 / 72 h	>110 mg/l (algae) (OECD 201)				
	NOEC / 72h	110 mg/l (algae) (OECD 201)				
	NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)				
	EbC50 / 72h	>110 mg/l (algae) (OECD 201)				
	NOEC/ 35d	9.4 mg/L (fish) (OECD 210)				
	LC50/ 35d	33.7 mg/L (fish) (OECD 210)				
	· 12.2 Persistence and degradability					
		thylen glycol dimethacrylate				
	Biodegradation	on 85 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)				
41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate						
	Biodegradation	on 24 % /28d (not defined) (OECD 301D)				
	131-57-7 Oxy	ybenzone				
	Biodegradation	on 60-70 % /28d (not defined)				
	80-62-6 meth	nyl methacrylate				
	Biodegradation	on 94 % /14d (not defined) (OECD 301C)				
	12.3 Bioaccu	imulative potential				

- Bloconcentration factor (BCF) | >33-<160 (fish) (OECD 305)
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.

131-57-7 Oxybenzone

- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
 - Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA

Void

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2022 Version number 4 (replaces version 3) Revision: 16.11.2022

Trade name: Signum matrix Matrix, Opal, MD, SD

		(Contd. of page
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accordin IMO instruments	g to Not applicable.	
· Transport/Additional information:	-	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or

No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.