

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LuxaBond Total Etch (bond A)

1.2. Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause respiratory irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

2.2. Label elements**Regulation (EC) No 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H335	May cause respiratory irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

Precautionary statements

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 2 of 5

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1565-94-2	Bis-GMA			15 - 25 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1565-94-2		Bis-GMA	15 - 25 %
		oral: LD50 = 5000 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Take up mechanically.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 3 of 5

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation of the storage area.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow
Odour:	like: ester

Changes in the physical state

Boiling point or initial boiling point and boiling range:	100 °C
point of decomposition:	> 200 °C
Flash point:	> 100 °C
pH-Value (at 20 °C):	4.5 - 7

Solubility in other solvents

Solubility ca. 50 %

Vapour pressure: (at 20 °C)	23 hPa
Density:	1,1 g/cm ³
Relative vapour density:	> 1

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 4 of 5

10.4. Conditions to avoid

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

LD50: Rat 5500mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1565-94-2	Bis-GMA				
	oral	LD50 mg/kg 5000	Rat	literature value	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information**12.1. Toxicity**

Aquatotoxicity LC50: > 360 mg / l / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of hazardous waste according to official regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 5 of 5

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Other applicable information**

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): - - non-hazardous to water

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Further Information

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LuxaBond Total Etch Bond B

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause respiratory irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

2.2. Label elements**Regulation (EC) No. 1272/2008**

Signal word: Danger

Pictograms:

**Hazard statements**

H335	May cause respiratory irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

Precautionary statements

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 2 of 5

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1565-94-2	Bis-GMA			15 - 25 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 3 of 5

8.1. Control parameters**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation of the storage area.

Protective and hygiene measures

When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow
Odour:	like: ester
pH-Value (at 20 °C):	4.5 - 7

Changes in the physical state

Initial boiling point and boiling range:	100 °C
point of decomposition:	> 200 °C
Flash point:	> 100 °C
Vapour pressure:	23 hPa
(at 20 °C)	
Density:	1,1 g/cm ³

Solubility in other solvents

Solubility ca. 50 %

Vapour density:	> 1
-----------------	-----

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 4 of 5

Acute toxicity

LD50: Rat 5500mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1565-94-2	Bis-GMA				
	oral	LD50 5000 mg/kg	Rat	literature value	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information**12.1. Toxicity**

Aquatic toxicity LC50: > 360 mg / l / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of hazardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Other applicable information**

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water contaminating class (D): - - not water contaminating

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 5 of 5

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Further Information

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LuxaBond Total Etch_Pre-bond

CAS No: 64-17-5
 Index No: 603-002-00-5
 EC No: 200-578-6

1.2. Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name: DMG Chemisch-Pharmazeutische Fabrik GmbH
 Street: Elbgaustraße 248
 Place: D-22547 Hamburg
 Telephone: +49. (0) 40. 84006-0
 e-mail: info@dmg-dental.com
 Internet: www.dmg-dental.com
 Telefax: +49. (0) 40. 84006-222

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

2.2. Label elements**Regulation (EC) No 1272/2008****Special labelling of certain mixtures**

EUH210 Safety data sheet available on request.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol; ethyl alcohol			55 - 99 %
	200-578-6	603-002-00-5		
	Flam. Liq. 2; H225			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	ethanol; ethyl alcohol	55 - 99 %
	inhalation: LC50 = 95,6 mg/l (vapours); oral: LD50 = 6200 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 2 of 6

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap. Change contaminated clothing. Rub greasy ointment into the skin.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

If swallowed, immediately drink: Water. Medical treatment necessary.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Atomized water. alcohol resistant foam. Carbon dioxide (CO₂). Extinguishing powder. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Concentrated vapors are heavier than air. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

The following must be prevented: inhalation. skin contact. Eye contact.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep away from sources of ignition - No smoking. Provide adequate ventilation.

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 3 of 6

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation. exceeding exposure limit values: Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless-transparent
Odour:	characteristic
Melting point/freezing point:	ca. -115 °C
Boiling point or initial boiling point and boiling range:	ca. 80 °C
Lower explosion limits:	3.5 vol. %
Upper explosion limits:	15 vol. %
Flash point:	The product has not been tested.
Auto-ignition temperature:	425 °C
pH-Value:	neutral
Water solubility:	complete miscible
Vapour pressure:	59 hPa
(at 20 °C)	
Density (at 20 °C):	ca. 0,8 g/cm ³
Viscosity / dynamic:	1,3 mPa·s
(at 20 °C)	

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat.

10.5. Incompatible materials

Oxidizing agents. peroxides. acid. Alkali metals.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Acute toxicity, oral LD50: (Rat): > 10000 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 4 of 6

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol; ethyl alcohol				
	oral	LD50 6200 mg/kg	Rat	IUCLID	
	inhalation (4 h) vapour	LC50 95,6 mg/l	Rat	RTECS	

Irritation and corrosivity

In case of prolonged or frequently repeated skin contact: irritant.; Following eye contact: irritant.

SECTION 12: Ecological information**12.1. Toxicity**

Acute fish toxicity (Leuciscus idus): LC50: > 8140 mg / l / 48 h (Ethanol);

Acute Daphnia toxicity (Daphnia magna): EC50: 9268 - 14221 mg / l / 48 h

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
64-17-5	ethanol; ethyl alcohol				
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h	Daphnia magna	IUCLID

12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	ethanol; ethyl alcohol			
	Biologische Abbaubarkeit	94 %		OECD 301E
	leicht biologisch abbaubar			
	Chemischer Sauerstoffbedarf	930-1670 mg/g	5	

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Remove according to the regulations.

List of Wastes Code - residues/unused products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 5 of 6

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH
(EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH
CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans;
chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1170
14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 144 601
 Limited quantity: 1 L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170
14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: 144
 Limited quantity: 3 L
 EmS: F-E, S-D

Other applicable information (marine transport)

E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170
14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 6 of 6

IATA-max. quantity - Cargo:

60 L

Other applicable information (air transport)

E2

: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
EUH210	Safety data sheet available on request.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)