

Page 1/10

Revision: 05.12.2024

Tel.: +49 (0)800 4372522

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company

undertaking · 1.1 Product identifier

- · Trade name: Signum metal bond I
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Metal-Resin Bonding System
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Informing department: E-Mail: msds@kulzer-dental.com

• 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
 - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210

No smoking.

P261 Avoid breathing mist/vapours/spray. P280 Wear protective gloves / eye protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards -

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 1)

- · Results of PBT and vPvB assessment
 - · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
 - · Description: -

Dangerous components:		
EINECS: 200-662-2 Index number: 606-001-00-8	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	>90%
	10-(Phosphonooxy)decyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0-5%
EINECS: 200-580-7 Index number: 607-002-00-6	acetic acid Flam. Liq. 3, H226 Skin Corr. 1A, H314; Eye Dam. 1, H318 (Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90 % Skin Corr. 1B; H314: 25 % ≤ C < 90 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %	≥1-<3%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact

Instantly rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
 - · Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information -

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with eyes and skin.

Use breathing protection against the effects of fumes/dust/aerosol.

- · 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Ensure adequate ventilation.

Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

-

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
 - · Storage
 - Requirements to be met by storerooms and containers: Store in cool location.
 - Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:
 - Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

GB



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection 8.1 Control parameters Components with critical values that require monitoring at the workplace:

Components with childen values that require monitoring at the workplace.		
67-64-1 acetone		
WEL (Great Britain)	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
IOELV (European Union)	Long-term value: 1210 mg/m³, 500 ppm	
64-19-7 acetic acid		
WEL (Great Britain)	Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm	
IOELV (European Union)	Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm	

· DNI	ELs			
67-64-1 acetone				
Oral	general population, long term, systemic	62 mg/Kg (not defined)		
Dermal	worker industrial, long term, systemic	186 mg/Kg/d (not defined)		
	general population, long term, systemic	62 mg/Kg/d (not defined)		
Inhalative	worker industrial, long term, systemic	1,210 mg/m3 (not defined)		
	worker industrial, long term, local	2,420 mg/m3 (not defined)		
	general population, long term, systemic	200 mg/m3 (not defined)		

· PNECs

67-64-1 acetone

freshwater
marine water
sewage treatment plant
sediment, dry weight, freshwater
soil, dry weight
freshwater
soil, dry weight
10.6 mg/l (not defined)
1.06 mg/l (not defined)
30.4 mg/Kg (not defined)
30.4 mg/Kg (not defined)
0.112 mg/Kg (not defined)

Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Filter AX.

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 4)

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

- Eye/face protection Tightly sealed safety glasses.
- Body protection:

Protective work clothing.

Light weight protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

Physical state
 Colour:
 Smell:
 Acetone-like

· **Odour threshold:** Not determined.
 Not determined

Boiling point or initial boiling point and

boiling range 55 °C

· Flammability Not applicable.

Lower and upper explosion limit

Lower: 2.6 Vol %

· Upper: 13.0 Vol %
· Flash point: -3 °C

Auto-ignition temperature: 465 °C (67-64-1 acetone)

· Decomposition temperature: Not determined.

SADT

· pH at 20 °C 5-6 · Viscosity:

· Kinematic viscosity
Not determined.
· Kinematic viscosity

· dynamic: Not determined.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 5)

Solubility

Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

Not determined. value)

Steam pressure at 20 °C: 247 hPa

Vapour pressure:

Density and/or relative density

Density Not determined Relative density Not determined. Not determined. · Vapour density

No further relevant information available. · 9.2 Other information

Appearance:

Form: Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures is possible.

· Change in condition Not determined. · Evaporation rate

· Information with regard to physical hazard

classes

Void **Explosives** · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Void

· Oxidising liquids Oxidising solids Void Organic peroxides Void Void Corrosive to metals · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
 - Conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known

(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 6)

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - · Additional information: -

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
 - · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
67-64-1 a	67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	>15,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	76 mg/l (rat)	
64-19-7 ad	64-19-7 acetic acid		
Oral	LD50	3,310 mg/kg (rat)	
Inhalative	LC50/4 h	11.4 mg/l (rat) (OECD 403)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· 11.2 Information on other hazards

· Endocrine disrupting properties	
128-37-0 2,6-di-tert-butyl-p-cresol	List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic t	toxicity:
67-64-1 acet	tone
EC50/48h	8,800 mg/l (daphnia)
LC50/96h	6,210 mg/l (fish) (OECD 203)
64-19-7 acet	tic acid
EC50/48h	>300.82 mg/l (daphnia) (OECD 202)
	(Contd. on page 8

n page ຮ



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 7)

LC50/96h >1,000 mg/l (fish) (OECD 203)

ErC50 / 72 h >1,000 mg/l (algae) NOEC / 72h 1,000 mg/l (algae)

NOEC / 96h | 1,000 mg/l (fish) (OECD 203)

· 12.2 Persistence and degradability

67-64-1 acetone

Biodegradation 90.9 % /28d (not defined) (OECD 301D)

64-19-7 acetic acid

Biodegradation 96 % /20d (not defined)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

• 12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1090

14.2 UN proper shipping name

ADR 1090 ACETONE solution
IMDG. IATA ACETONE solution

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 8) · 14.3 Transport hazard class(es) ADR · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA ·Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMĎĞ, IATA II· 14.5 Environmental hazards: Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Kemler Number: *3*3 F-E,S-D · EMS Number: · Stowage Category · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L Excepted quantities (ÉQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 1L Excepted quantities (ÉQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml (Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 9)

UN "Model Regulation":

UN 1090 ACETONE SOLUTION, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.



Page 1/13

Safety data sheet according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 29.07.2024 Revision: 29.07.2024

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
 - · Trade name: Signum metal bond II
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Metal-Resin Bonding System
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· Informing department: E-Mail: msds@kulzer-dental.com

· 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Highly flammable liquid and vapour. Flam. Liq. 2 H225

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 May cause an allergic skin reaction. H317

H360Fd May damage fertility. Suspected of damaging the unborn child. Repr. 1B

STOT SE 3 May cause respiratory irritation. H335

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
 - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS02 GHS07 GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate tert-butyl perbenzoate

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)



Page 2/13

Safety data sheet according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 29.07.2024 Revision: 29.07.2024

Trade name: Signum metal bond II

(Contd. of page 1)

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210

No smoking.

P273 Avoid release to the environment.

Wear protective gloves / eye protection. P280

P280 Wear protective clothing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Store locked up.

· Additional information:

Restricted to professional users.

2.3 Other hazards -

P405

· Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: -

· Dangerous components:		
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥50-≤75%
CAS: 72869-86-4 EINECS: 276-957-5 Index number: 607-134-00-4 Reg.nr.: 01-2120751202-68-xxxx	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate Aquatic Chronic 2, H411 Skin Sens. 1B, H317 EUH204	≥10-<25%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X Reg.nr.: 01-2119972295-29-xxxx	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 1B, H360Fd Aquatic Chronic 2, H411 Skin Sens. 1B, H317	1-<3%
CAS: 614-45-9 EINECS: 210-382-2	tert-butyl perbenzoate Org. Perox. C, H242 Aquatic Acute 1, H400 Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥0.1-<0.25%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 3)



Page 3/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

(Contd. of page 2)

Revision: 29.07.2024

Trade name: Signum metal bond II

• After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

· Protective equipment: Wear self-contained breathing apparatus.

· Additional information -

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with eyes and skin.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Do not allow to enter the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

-

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



Page 4/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 6 (replaces version 5)

Revision: 29.07.2024

Trade name: Signum metal bond II

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
 - · Storage

Dermal

Inhalative

- · Requirements to be met by storerooms and containers: Store in cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

worker industrial, long term, systemic

worker industrial, long term, systemic

- Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Compo	onents with cri	tical values that require	monitoring at the workplace:	
	ethyl methacry	/late		
		Short-term value: 416 m Long-term value: 208 m		
IOELV (Ει	ıropean Union)	Short-term value: 100 pp Long-term value: 50 ppn	орт	
· DNI	ELs			
80-62-6 m	ethyl methacry	ylate		
Oral	general popula	tion, long term, systemic	8.2 mg/Kg (not defined)	
Dermal	worker industri	al, long term, systemic	13.67 mg/Kg/d (not defined)	
	general popula	tion, long term, systemic	8.2 mg/Kg/d (not defined)	
Inhalative	worker industri	al, acute, local	416 mg/m3 (not defined)	
	worker industri	al, long term, systemic	348.4 mg/m3 (not defined)	
	worker industri	al, long term, local	208 mg/m3 (not defined)	
	general popula	tion, acute, local	208 mg/m3 (not defined)	
	general population, long term, systemic 74.3 mg/m3 (not defined)			
72869-86-	bismethacry	late	xo-3,14-dioxa-5,12-diazahexadecane-1,16-d	
Oral		tion, long term, systemic		
Dermal		-	1.3 mg/Kg/d (not defined)	
	general popula		0.7 mg/Kg/d (not defined)	
Inhalative	worker industri	al, long term, systemic	3.3 mg/m3 (not defined)	
	general popula	tion, long term, systemic	0.6 mg/m3 (not defined)	
75980-60-	8 diphenyl(2,4	,6-trimethylbenzoyl)pho	sphine oxide	
Oral		-	0.0833 mg/Kg (not defined)	

general population, long term, systemic 0.0833 mg/Kg/d (not defined)

general population, long term, systemic 0.145 mg/m3 (not defined)

0.233 mg/Kg/d (not defined)

0.822 mg/m3 (not defined)

(Contd. on page 5)



Page 5/13

Safety data sheet according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 29.07.2024 Revision: 29.07.2024

Trade name: Signum metal bond II

	(Contd. of page 4)
· PNECs	
80-62-6 methyl methacrylate	
freshwater	0.94 mg/l (not defined)
marine water	0.094 mg/l (not defined)
sewage treatment plant	10 mg/l (not defined)
sediment, dry weight, freshwater	10.2 mg/Kg (not defined)
sediment, dry weight, marine water	0.102 mg/Kg (not defined)
soil, dry weight	1.48 mg/Kg (not defined)
72869-86-4 7,7,9(or 7,9,9)-trime bismethacrylate	thyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl
freshwater	0.01 mg/l (not defined)
marine water	0.001 mg/l (not defined)
sewage treatment plant	3.61 mg/l (not defined)
sediment, dry weight, freshwater	4.56 mg/Kg (not defined)
sediment, dry weight, marine water	0.46 mg/Kg (not defined)
soil, dry weight	0.91 mg/Kg (not defined)
75980-60-8 diphenyl(2,4,6-trimeth	ylbenzoyl)phosphine oxide
freshwater	0.0014 mg/l (not defined)
marine water	0.00014 mg/l (not defined)
sediment, dry weight, freshwater	0.115 mg/Kg (not defined)
sediment, dry weight, marine water	0.0115 mg/Kg (not defined)
soil, dry weight	0.0222 mg/Kg (not defined)

[·] Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment

General protection measures, such as personal prote General protective and hygienic measures Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

(Contd. on page 6)



Page 6/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

Revision: 29.07.2024

Trade name: Signum metal bond II

Material of gloves

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

Eve/face protection Safety glasses

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid · Colour: White

· Smell: Characteristic Not determined. Odour threshold:

· Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 100 °C

· Flammability Not applicable.

Lower and upper explosion limit

2.1 Vol % Lower: 12.5 Vol % Upper:

· Flash point: 10 °C (80-62-6 methyl methacrylate)

· Auto-ignition temperature: 430 °C

· Decomposition temperature: Not determined.

·SAPT

Signum metal bond II > 60 °C

·SADT

· pH

Mixture is non-soluble (in water). Viscosity:

· Kinematic viscosity Not determined. · Kinematic viscosity

· dynamic: Not determined.

Solubility · Water:

Partition coefficient n-octanol/water (log

Not determined. value)

47 hPa Steam pressure at 20 °C:

(Contd. on page 7)

Not miscible or difficult to mix



Page 7/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version number 6 (replaces version 5) Revision: 29.07.2024

Trade name: Signum metal bond II

(Contd. of page 6)

· Vapour pressure:

Density and/or relative density

Density
 Relative density
 Vapour density
 Not determined.
 Not determined.
 Not determined.

· 9.2 Other information

No further relevant information available.

· Appearance:

Fluid

Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures is possible.

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard classes

· Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void

• Flammable liquids Highly flammable liquid and vapour.
• Flammable solids Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void

SECTION 10: Stability and reactivity

· Desensitised explosives

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
 - Conditions to be avoided: No decomposition if used and stored according to specifications.

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

(Contd. on page 8)



Page 8/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

Revision: 29.07.2024

Trade name: Signum metal bond II

(Contd. of page 7)

· Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
 - · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
	80-62-6 methyl methacrylate		
Oral	LD50	~7,900 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)	
Inhalative	LC50/4 h	29.8 mg/l (rat)	
72869-86-	72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	
75980-60-	8 dipheny	l(2,4,6-trimethylbenzoyl)phosphine oxide	
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	
614-45-9 t	614-45-9 tert-butyl perbenzoate		
Oral	LD0	2,000 mg/kg (rat) (OECD 423)	
Dermal	LD0	2,000 mg/kg (rat) (OECD 402)	
Inhalative	LC0/4h	1.01 mg/L (rat) (OECD 439)	
	LC100/4h	4.9 mg/L (rat) (OECD 439)	

· Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

May damage fertility. Suspected of damaging the unborn child.

STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
 - · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 Repr. 1B

(Contd. on page 9)



Page 9/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

Revision: 29.07.2024

Trade name: Signum metal bond II

· 11.2 Information on other hazards	(Contd. of page 8)
Endocrine disrupting properties	
128-37-0 2 6-di-tert-hutyl-n-cresol	l ist II

SECTION 12: Ecological information

49 mg/L (daphnia) (OECD 211)

· 12.1 Toxicity

EC50/21d

· Aquatic toxicity:

80-62-6 methyl methacrylate

EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)	
NOEC / 21d	37 mg/l (daphnia) (OECD 211)	
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)	
NOEC / 72h	110 mg/l (algae) (OECD 201)	
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)	
EbC50 / 72h	>110 mg/l (algae) (OECD 201)	
NOEC/ 35d	9.4 mg/L (fish) (OECD 210)	
LC50/ 35d	33.7 mg/L (fish) (OECD 210)	
72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl		
bismethacrylate		
EC50/48h	>1.2 mg/l (daphnia) (OECD 202)	
LC50/96h	10.1 mg/l (fish) (OECD 203)	
ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)	
NOEC / 72h	0.21 mg/l (algae) (OECD 201)	
75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide		
EC50/48h	10,100 mg/l (algae)	
	3.53 mg/l (daphnia) (OECD 202)	
LC50/96h	1.4 mg/l (fish) (OECD 203)	
ErC50 / 72 h	>2.01 mg/l (algae) (OECD 201)	
ErC10/72h	1.56 mg/L (algae) (OECD 201)	

· 12.2 Persistence and degradability

80-62-6 methyl methacrylate

Biodegradation 94 % /14d (not defined) (OECD 301C)

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

Biodegradation 22 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Biodegradation 0-10 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)

· 12.3 Bioaccumulative potential

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Bloconcentration factor (BCF) 47-55 (not defined)

(Contd. on page 10)



Page 10/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

Revision: 29.07.2024

Trade name: Signum metal bond II

(Contd. of page 9)

- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
 - · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packagings:
 - Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S., speci provision 640D (METHYL METHACRYLAT MONOMER, STABILIZED, 7,7,9(or 7,9,9 trimethyl-4,13-dioxo-3,14-dioxa-5,12 diazahexadecane-1,16-diyl bismethacrylate)
· IMDG	FLAMMABLE LIQUID, N.O.S. (METH) METHACRYLATE MONOMER, STABILIZE 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-diox 5,12-diazahexadecane-1,16-di bismethacrylate), MARINE POLLUTANT
·IATA	FLAMMABLE LIQUID, N.O.S. (METHY METHACRYLATE MONOMER, STABILIZED 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo5,12-diazahexadecane-1,16-diy bismethacrylate)

(Contd. on page 11)



Page 11/13

Revision: 29.07.2024

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

Trade name: Signum metal bond II

(Contd. of page 10) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. ·Label · IMDG · Class 3 Flammable liquids. · Label ·IATA · Class 3 Flammable liquids. · Label 14.4 Packing group ADR, IMDG, IATA II· 14.5 Environmental hazards: Marine pollutant: No Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): · 14.6 Special precautions for user Warning: Flammable liquids. 33 Kemler Number: · EMS Number: F-E,S-E · Stowage Category · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L (Contd. on page 12)



Page 12/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024 Version num

Version number 6 (replaces version 5) Revision: 29.07.2024

Trade name: Signum metal bond II

	(Contd. of page 11)
· Excepted quantities (EQ) · Transport category · Tunnel restriction code	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED, 7,7,9(OR 7,9,9)-TRIMETHYL- 4,13-DIOXO-3,14-DIOXA-5,12- DIAZAHEXADECANE-1,16-DIYL BISMETHACRYLATE),3,II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
 - · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H242 Heating may cause a fire.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

(Contd. on page 13)



Page 13/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 6 (replaces version 5)

Revision: 29.07.2024

(Contd. of page 12)

Trade name: Signum metal bond II

· Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature SAPT: Self Accelerating Polymerisation Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Ltq. 2: Flammable liquids — Category 2
Org. Perox. C: Organic peroxides — Type C/D
Acute Tox. 4: Acute toxicity — Category 4
Skin Irrit. 2: Skin corrosion/irritation — Category 2
Skin Sens. 1: Skin sensitisation — Category 1
Skin Sens. 1B: Skin sensitisation — Category 1B
Repr. 1B: Reproductive toxicity — Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) — Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic ha

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.