

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UNIFAST Trad Liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven

Tel. +32/(0)16/74.10.00 Fax +32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02

GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 1)

### · Hazard-determining components of labelling:

Methyl methacrylate

2-(2H-benzotriazol-2-yl)-p-cresol Ethyleneglycol dimethacrylate

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P272 Contaminated work clothing should not be allowed out of the workplace.

*P280* Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

### · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 80-62-6	Methyl methacrylate	90-<100%
EINECS: 201-297-1 Index number: 607-035-00-6	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3. H335	
	substance with a Community workplace exposure limit	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	1-<2.5%
EINECS: 202-805-4 Index number: 612-296-00-4	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	
	ATE: LD50 oral: 140 mg/kg LC50/4 h inhalative: 1.4 mg/l	
C45 2440 22 4	6	1 < 2.50/
CAS: 2440-22-4 EINECS: 219-470-5	2-(2H-benzotriazol-2-yl)-p-cresol Acute Tox. 3, H331; Aquatic Chronic 1, H410; Skin Sens. 1, H317	1-<2.5%
CAS: 97-90-5	Ethyleneglycol dimethacrylate	0.2-<0.5%
EINECS: 202-617-2 Index number: 607-114-00-5	Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: $C \ge 10 \%$	
CAS: 123-31-9	hydroquinone	≥0.025-<0.1%
EINECS: 204-617-8 Index number: 604-005-00-4	Muta. 2, H341; Carc. 2, H351; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Acute Tox. 4, H302; Skin Sens. 1, H317	
		(Contd. on page 3)

(Contd. on page 3)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Do not use mouth to mouth or mouth to nose resuscitation.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

*If skin irritation continues, consult a doctor.* 

· After eve contact:

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

*If symptoms persist consult doctor.* 

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

(Contd. on page 4)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 3)

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

### · 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

	Ingredients with	h limit values that	require monitorin	g at the workplace:
--	------------------	---------------------	-------------------	---------------------

### 80-62-6 Methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

### · DNELs

### 80-62-6 Methyl methacrylate

Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)
T 1 1	DATES 1 1	200 ( 2 ( : ) ( 1 1

Inhalative | DNEL inhalation | 208 mg/m3 (air) (worker, l. te., syst.)

(Contd. on page 5)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 4)

· PNECs

### 99-97-8 N,N-dimethyl-p-toluidine

PNEC Aqua | 152.59 µg/L (freshwater)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Hand protection



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Odour threshold:
Fluid
Yellow
Characteristic
Not determined.

• Odour threshold:
• Melting point/freezing point:
• Not determine
-48 °C

· Boiling point or initial boiling point and boiling range 100 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: 10 °C

· Auto-ignition temperature: Undetermined. · Decomposition temperature: Not determined.

(Contd. on page 6)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

	(Contd. of pag
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	0.6 mPas
Solubility	
water at 20 °C:	0.15  g/l
	Insoluble.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	$0.9 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Liquid
Important information on protection of health a environment, and on safety.	and
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	Γ
VOC (EC)	$0.0~\mathrm{g/l}$
Change in condition	<u> </u>
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable ga.	
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Oxidising solds Organic peroxides	Void
Organic peroxiaes Corrosive to metals	voia Void
	voia Void
Desensitised explosives	v 0เน

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 6)

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
80-62-6 M	80-62-6 Methyl methacrylate		
Oral	LD50	6,000 mg/kg (rabbit)	
Dermal	LD50	>5,000 mg/kg (rab)	
Inhalative	LC50/4 h	29.8  mg/l  (rat  (f+m))	
99-97-8 N,	N-dimethy	yl-p-toluidine	
Oral	LD50	140 mg/kg (ATE)	
		1,650 mg/kg (rat (f+m))	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	1.4 mg/l (ATE)	
		1.4  mg/l  (rat  (f+m))	
2440-22-4	2-(2H-ben	nzotriazol-2-yl)-p-cresol	
Oral	LD50	10,000 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	0.59  mg/l  (rat  (f+m))	
97-90-5 Et	97-90-5 Ethyleneglycol dimethacrylate		
Oral	LD50	8,700 mg/kg (rat (f+m))	
Dermal	LD50	>2,000 mg/kg (rat (f+m))	

- Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

· 11.2 Information on other hazards

· Endocrin	e disrupting properties
128-37-0	Butylated hydroxytoluene

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### 99-97-8 N,N-dimethyl-p-toluidine

LC50/96h 46 mg/L (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 8)

List II

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 7)

- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1247
	01(124)
14.2 UN proper shipping name	10.45 NEWWY METH CRAN ATE MONOME
ADR	1247 METHYL METHACRYLATE MONOME.
HADO LATA	STABILIZED
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

	(Contd. of page
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	C
Stowage Code	SW1 Protected from sources of heat.
3	SW2 Clear of living quarters.
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	Temperature control is not required, in regards to Special Provision 386. Product uses chemical stabilization.
ADR	
Limited quantities (LQ)	IL
Excepted quantities $(EQ)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
<i>IMDG</i>	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMEI STABILIZED, 3, II

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST Trad Liquid

(Contd. of page 9)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

### · Classification according to Regulation (EC) No 1272/2008 Calculation method

- · **Department issuing SDS:** Regulatory affairs
- · Contact: msds@gc.dental

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 2: Germ cell mutagenicity - Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

#### Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

(Contd. on page 11)

Printing date 30.06.2025 Version number 5 (replaces version 4) Revision: 30.06.2025

Trade name: UNIFAST\_Trad\_Liquid

(Contd. of page 10)

### \* \* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GB